

PROFESSIONAL APPLICATOR INSTRUCTIONS

Professional Applicator makes it easy to apply: **Roof QSE, Roof OX** and **Roof Armor** from a distance with your garden hose.

Detailed Assembly and mix ratio instructions are included on the white sprayer instruction page.

Unfold for Directions



Reorder - Questions? - Send a Photo CleanerToday.com/QR-app or SCAN





GENERAL

Which Tip to use?

NO TIP (BEST)

By removing either/ both tips, the applicator can project stream of cleaner up to 25 feet (Distance varies based water pressure / PSI, effected by hose diameter, household pressure, roof pitch and height)

Deflector tip

Close up spray approx 3 ft width and 3ft out

Foam Wand

Not used with Cleaner Today products, but can be used with a foaming car wash soap

TIPS / HINTS

- ⇒ USE Roof Armor every year to prevent stains if you purchased the Clean Roof Forever bundle, follow tan Roof Armor Treatment instructions
 - ⇒ If you do not have Roof Armor Treatment, it's not too late! Apply anytime with 12 months
- Practice spraying with plain water before using the cleaner, practice can help avoid wasting the cleaner
- ⇒ BEST results are from applying and rinsing from the roof
- ⇒ Good results can be obtained from the gutter line, but heavy stains will longer to fade
- ⇒ Never spray from the ground, the roof cleaners may land on unintended surfaces

ROOF QSE

Mixing Roof QSE:

- ◆ Use Gloves and Face Protection
- ♦ Fill 1/3 of spray jar with water
- Add contents of 1 (one)
 QSE EZ-Pouch while stirring
- ◆ Mix until dissolved
- Spray jar will become HOT, this is normal, the cleaner releases heat
- Fill with water to top of jar
- Attach applicator to jar, then to hose
- ◆ Set applicator dial to 'E' (12oz / gal)
- ◆ Continue with 'APPLY' step on BLUE Roof QSE instructions

Notes regarding Roof QSE:

- Handle carefully, cleaner is HIGHLY concentrated in jar
- Cleaner will dispense about 7 minutes before jar is empty, this should be used to cover 750 sq ft
- If cleaner is not dispensing, shake spray jar, un-dissolved cleaner may block the siphon tube

ROOF ARMOR

Mixing Roof Armor:

- Roof Armor Treatment powered by: MoldSTAT Plus
- Mold STAT plus is packaged in either a 16oz dispenser or 1 Gallon Jug.
- ◆ Add 16oz or 2 cups of MoldSTAT Plus to spray jar
- ♦ Add 24oz or 3 cups water to spray jar

Spraving Roof Armor:

- ◆ Set Dial to "B" (2oz / gallon)
- Attach to hose, remove applicator tip for long range stream
- Soak roof ensuring that that every area is treated (wet)
- ♦ Makes 20 gal / covers 3000 sg ft

Rinsing:

- Rising is not required
- ◆ Treatment prevents the formation of roof stains for 12 - 15 months



Roof Armor Treatment Every 12 months

ROOF OX

Mixing Roof OX:

- Use Gloves
- ◆ Fill 1/3 of spray jar with **HOT** water
- ◆ Slowly stir in contents of 1 (one) OX EZ-Pouch
- ◆ Jar will foam during this time, as water activates the oxygen reaction
- ◆ Fill remainder of jar with **HOT** water
- ♦ Wait 5 minutes for activation
- ◆ Attach applicator to jar, then to hose
- ◆ Set applicator dial to 'E' (12oz / gal)
- ◆ Continue with 'APPLY' step on Roof OX instructions

Notes regarding Roof OX:

- Dispensing the cleaner will take approx 7 minutes, you should cover a 325 sq ft area in this time
- If cleaner is not dispensing, shake spray jar, un-dissolved cleaner may block siphon tube